

Timber deck for heavy loadings GSA®- TCD-System

n'H-Timber beams with GSA®-shear connectors
Chart only to be used for pre-calculations
 jus/V1.01/10.10.13-E



| Live Load q_{LL} | 2.0kN/m ² | 3.0kN/m ² | 5.0kN/m ² |
|--------------------|----------------------|----------------------|----------------------|
| span [m] | dimension [mm] | dimension [mm] | dimension [mm] |
| 7.0 | 200/240 | 200/240 | 200/280 |
| 8.0 | 200/280 | 200/280 | 200/320 |
| 9.0 | 200/320 | 200/320 | 240/360 200/400 |
| 10.0 | 240/360 200/400 | 240/360 200/400 | 240/400 200/440 |
| 11.0 | 240/400 200/440 | 240/400 200/440 | 240/440 200/480 |
| 12.0 | 240/440 200/480 | 240/440 200/480 | 240/480 200/520 |
| more than 13.0 | on demand | on demand | on demand |

base:

| | |
|---------------------------------|--|
| Criteria | ULS and SLS according to Eurocode |
| Self weight of deck | $g_k = 3.5 \text{ kN/m}^2$ |
| Dead Load | $q_{DL} = 2.0 \text{ kN/m}^2$ |
| Spacing of beams | 1.0 m |
| Depth of concrete | $h = 120 \text{ mm}$ |
| Service class | 1 |
| System | single span (with applied precamber) |
| Fire resistance | REI 60 |
| Noise protection ⁽¹⁾ | $L'_{n,w} = 47 - 32 \text{ dB (Impact)}$ |
| Noise protection ⁽¹⁾ | $R'_w = 62 - 64 \text{ dB (Airborne)}$ |

Additional basic conditions such as support of beams, general details, quality of concrete, concrete reinforcements etc. : To be determined by engineering office or n'H.

Vibrations according to P. Hamm – Konstruktionsregeln für die Praxis, 2. Internationales Forum Holzbau Beaune 2012

⁽¹⁾ Floor composition: Cement screed and insulation (mineral fibre)